




College of Agriculture

EU- Erasmus + /Benefit Project

EU Project 609544-EPP-1-2019-1-PS-EPPKA2-CBHE-JP

The needed equipment's of Hebron University

Item	Specifications	Quantity	Price
Vo2 max analyzer	Self-Calibrating - Measure pressure, temperature, and humidity, Heart rate, and volume and gas concentrations of inspired and expired air - Equipped with oxygen sensor - Equipped with Hans Rudolf Face Mask - Equipped with original batteries and spare batteries - Equipped with 3 different size ventilation pieces - On/Off button, RGB LED indicator, phone and tablet application - Wireless and Bluetooth capability - O2 Accuracy $\pm 1\%$ - Flow Accuracy $\pm 3\%$ - Flow Sensor: Type Differential Pressure - Oxygen Sensor Type: Galvanic Fuel Cell	1	
Thermo Scientific™ Sorvall ST8R Centrifuge 75007204	Permissible Ambient Temperature during Operation $+2\text{ }^{\circ}\text{C}$ to $+35\text{ }^{\circ}\text{C}$ Maximum Speed n max 17850 rpm Minimum Speed nmin 300 rpm Maximum RCF Value at n max 30279 x g Temperature Setting Range $-10\text{ }^{\circ}\text{C}$ to $+40\text{ }^{\circ}\text{C}$ Dimensions Height (open door / closed door) 700 mm / 320 mm Width: 460 mm Depth: 670 mm Weight: 74 kg	1	
Sartorius Cubis® Micro Balances, 1.1   2.1   3.1 g Capacity 	Balance Type: Micro balance Capacity: 1.1   2.1   3.1 g Readability: 0.001   0.002   0.005 mg Reproducibility: $\pm 1.0$   2.0   5.0 mg Linearity: $\pm 4.0\text{mg}$ Pan Size (mm/in): 30 / 1.2 Calibration Type: isoCAL Calibration Weight (g): 2 + 1 (custom weight set required) Shipping Weight: 28 lbs	1	

<p>3 IN 1 DIGITAL TESTER (PH, EC, TEMPERATURE)</p> 	<p>Waterproof Standard IP65 Replaceable electrode Immediately ready for use Temperature displayed in degrees Celsius and Fahrenheit <u>PH: 0.00-14.00</u> <u>EC: 0.00-19.99 (equal to 19990 us / cm)</u> <u>Temperature: -50°C – + 70°C (-58°F – + 158°F)</u></p>	2	
<p><b>Hotplate Magnetic Stirrer</b> <b>Labnet AccuPlate™ Hotplate Stirrer</b></p> <p>D0420-230V</p> 	<p>Temperature Range: 5° - 550°C Temperature accuracy: ± 2°C Speed range: 60 - 1150 rpm Top Plate Material : Ceramic Top Plate Size: 12.7 x 17.8 cm (5" x 7") Dimensions (W x D x H) : 19.7 x 28 x 10.8 cm Weight: 3.2 kg (7.0 lbs.) Electrical : 230V, 50/60 Hz</p>	2	

معلومات الشركة المتقدمة

اسم الشركة:

رقم الهاتف:

الختم والتوقيع: